

# Technical sheet

## BERGAMO low cut safety shoes

Product code: 3165-S1P



<b>upper</b>	brushed cow suede leather, coated in a thickness of 1,8 - 2,0 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	lightweight polyurethan foam, coated with textile MESH, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1P SRA- with composite toe cap and kevlar midsole

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	Yes
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,81 kg	0,99 kg	200 mm	315 mm	115 mm	420 mm	590 mm	335 mm	10,60 kg	0,0 mm
37	0,87 kg	1,04 kg	200 mm	315 mm	115 mm	420 mm	590 mm	335 mm	11,00 kg	0,0 mm
38	0,91 kg	1,06 kg	200 mm	315 mm	115 mm	420 mm	590 mm	335 mm	11,20 kg	0,0 mm
39	0,93 kg	1,08 kg	200 mm	315 mm	115 mm	420 mm	590 mm	335 mm	11,40 kg	0,0 mm
40	0,94 kg	1,14 kg	200 mm	315 mm	115 mm	420 mm	590 mm	335 mm	12,00 kg	0,0 mm
41	0,98 kg	1,17 kg	200 mm	315 mm	115 mm	420 mm	590 mm	335 mm	12,40 kg	0,0 mm
42	1,01 kg	1,19 kg	200 mm	315 mm	115 mm	420 mm	590 mm	335 mm	12,60 kg	0,0 mm
43	1,04 kg	1,24 kg	200 mm	330 mm	120 mm	430 mm	620 mm	350 mm	12,80 kg	0,0 mm
44	1,05 kg	1,27 kg	200 mm	330 mm	120 mm	430 mm	620 mm	350 mm	13,20 kg	0,0 mm
45	1,09 kg	1,28 kg	200 mm	330 mm	120 mm	430 mm	620 mm	350 mm	13,60 kg	0,0 mm
46	1,10 kg	1,40 kg	210 mm	350 mm	125 mm	445 mm	655 mm	375 mm	14,60 kg	0,0 mm
47	1,19 kg	1,41 kg	210 mm	350 mm	125 mm	445 mm	655 mm	375 mm	14,80 kg	0,0 mm
48	1,26 kg	1,43 kg	210 mm	350 mm	125 mm	445 mm	655 mm	375 mm	15,00 kg	0,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	BD

<b>Weight</b>	1,45 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1