

# Technical sheet

## KORFU low cut safety shoes



Product code: 2015-S3ESD



<b>upper</b>	brushed, breathable poromeric microfiber material in combination with textile
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	35 - 49
<b>standard</b>	EN ISO 20345:2011, EN ISO 61340-5-1:2016
<b>version</b>	S3 ESD SRC - with plastic toe cap, and kevlar midsole, hydrophobic, antistatic properties ESD, NON METALLIC

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	Yes
<b>ESD</b> antistatic properties ESD	Yes
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S3

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
34	0,69 kg	0,92 kg	200 mm	315 mm	115 mm	42 mm	600 mm	340 mm	9,70 kg	220,0 mm
35	0,70 kg	0,94 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	10,20 kg	225,3 mm
36	0,71 kg	0,95 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	10,40 kg	231,0 mm
37	0,73 kg	0,96 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	10,50 kg	237,7 mm
38	0,77 kg	1,03 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	10,80 kg	244,3 mm
39	0,79 kg	1,04 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	11,00 kg	251,0 mm
40	0,83 kg	1,06 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	11,40 kg	257,7 mm
41	0,85 kg	1,09 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	11,80 kg	264,3 mm
42	0,91 kg	1,14 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	12,00 kg	271,0 mm
43	0,93 kg	1,18 kg	205 mm	330 mm	120 mm	430 mm	615 mm	345 mm	12,60 kg	277,7 mm
44	0,95 kg	1,22 kg	205 mm	330 mm	120 mm	430 mm	615 mm	345 mm	12,80 kg	284,3 mm
45	0,97 kg	1,24 kg	205 mm	330 mm	120 mm	430 mm	615 mm	345 mm	13,00 kg	291,0 mm
46	1,00 kg	1,28 kg	210 mm	350 mm	125 mm	440 mm	635 mm	360 mm	13,60 kg	299,7 mm
47	1,06 kg	1,33 kg	210 mm	350 mm	125 mm	440 mm	635 mm	360 mm	14,40 kg	304,4 mm
48	1,13 kg	1,40 kg	210 mm	350 mm	125 mm	440 mm	635 mm	360 mm	14,80 kg	311,0 mm
49	1,29 kg	1,48 kg	210 mm	350 mm	125 mm	440 mm	635 mm	360 mm	15,80 kg	317,7 mm
50	1,31 kg	1,49 kg	210 mm	360 mm	115 mm	450 mm	650 mm	375 mm	16,40 kg	323,3 mm

## **Business parameters**

**Tarric** 64041990  
**Country** CN  
**Weight** 1,15 kg  
**Add Unit** NPR  
**Add Quantity** 1