

# Technical sheet

## LUSAKA low cut outdoor shoes black

Product code: 4445-60



<b>upper</b>	synthetic, brushed EKO VELOUR material, leather combined with textile
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	EVA/RUBBER - glued construction
<b>size</b>	36 - 48
<b>usability</b>	shoes suitable for daily wear and outdoor activities
<b>version</b>	black colour

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	No
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	No
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	No
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	No
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,53 kg	0,73 kg	200 mm	300 mm	110 mm	425 mm	580 mm	320 mm	11,40 kg	240,0 mm
37	0,55 kg	0,75 kg	200 mm	300 mm	110 mm	425 mm	580 mm	320 mm	11,80 kg	247,0 mm
38	0,58 kg	0,78 kg	200 mm	300 mm	110 mm	425 mm	580 mm	320 mm	12,00 kg	253,0 mm
39	0,59 kg	0,80 kg	200 mm	300 mm	110 mm	425 mm	580 mm	320 mm	12,20 kg	260,0 mm
40	0,62 kg	0,82 kg	200 mm	300 mm	110 mm	425 mm	580 mm	320 mm	12,60 kg	267,0 mm
41	0,65 kg	0,86 kg	200 mm	320 mm	110 mm	425 mm	610 mm	320 mm	12,80 kg	273,0 mm
42	0,67 kg	0,89 kg	200 mm	320 mm	110 mm	425 mm	610 mm	320 mm	13,00 kg	280,0 mm
43	0,71 kg	0,95 kg	200 mm	320 mm	110 mm	425 mm	610 mm	320 mm	13,60 kg	286,0 mm
44	0,74 kg	1,01 kg	200 mm	320 mm	110 mm	425 mm	610 mm	320 mm	14,20 kg	293,0 mm
45	0,77 kg	1,05 kg	210 mm	370 mm	130 mm	445 mm	685 mm	395 mm	14,40 kg	300,0 mm
46	0,80 kg	1,10 kg	210 mm	370 mm	130 mm	445 mm	685 mm	395 mm	14,60 kg	306,0 mm
47	0,83 kg	1,15 kg	210 mm	370 mm	130 mm	445 mm	685 mm	395 mm	15,60 kg	313,0 mm
48	0,85 kg	1,18 kg	210 mm	370 mm	130 mm	445 mm	685 mm	395 mm	15,80 kg	320,0 mm

## Business parameters

<b>Tarric</b>	64041990
<b>Country</b>	BD
<b>Weight</b>	1,07 kg
<b>Add Unit</b>	NPR

**Add Quantity** 1