

Technical sheet

MONTGOMERY low cut safety shoes

Product code: 6345-S1P



upper	abrasion resistant textile
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped lightweight polyuretane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
size	39 - 47
standard	EN ISO 20345:2011
version	S1P SRC - with composite toe cap and kevlar midsole

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,03 kg	1,31 kg	215 mm	320 mm	115 mm	440 mm	590 mm	340 mm	13,80 kg	257,0 mm
40	1,08 kg	1,36 kg	215 mm	320 mm	115 mm	440 mm	590 mm	340 mm	14,40 kg	263,7 mm
41	1,13 kg	1,47 kg	215 mm	320 mm	115 mm	440 mm	590 mm	340 mm	14,80 kg	270,3 mm
42	1,18 kg	1,47 kg	215 mm	320 mm	115 mm	440 mm	590 mm	340 mm	15,40 kg	277,0 mm
43	1,19 kg	1,51 kg	225 mm	350 mm	125 mm	465 mm	640 mm	375 mm	16,20 kg	283,7 mm
44	1,22 kg	1,54 kg	225 mm	350 mm	125 mm	465 mm	640 mm	375 mm	16,40 kg	290,3 mm
45	1,28 kg	1,59 kg	225 mm	350 mm	125 mm	465 mm	640 mm	375 mm	16,80 kg	297,0 mm
46	1,35 kg	1,66 kg	225 mm	350 mm	125 mm	465 mm	640 mm	375 mm	17,40 kg	303,7 mm
47	1,37 kg	1,69 kg	225 mm	350 mm	125 mm	465 mm	640 mm	375 mm	17,80 kg	310,3 mm

Business parameters

Tarric	64041990
Country	CN
Weight	1,45 kg
Add Unit	NPR
Add Quantity	1