

Technical sheet

VERONA low cut occupational shoes TACTICAL

Product code: 6475-02



| | |
|---------------------|---|
| upper | dry mild cowhide leather in a thickness of 1,9 - 2,1 mm |
| lining | breathable thermo-insulation MEMBRANE FREE-TEX® |
| inner insole | expanded polyurethane of high absorbency, antistatic |
| outsole | PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, antistatic |
| size | 39 - 47 |
| standard | EN ISO 20347:2012 |
| version | O2 FO HRO SRC WR - without composite toe cap and kevlar midsole, hydrophobic, FREE-TEX® |

Properties

| | |
|---|------------|
| PL Midsole penetration protection nonmetallic - PL | No |
| PS Midsole penetration protection nonmetallic - PS | No |
| SR Antislip prop. on ceramic with glycerol | No |
| WPA Water resistant upper | No |
| HRO Resist. of the outsole against contact heat | Yes |
| WR Water resistant | Yes |
| WRU Water resistant upper | Yes |
| CI Insulation against cold | No |
| HI Insulation of the outsole against heat | No |
| FO Resist. of the outsole against fuel oils | Yes |
| P Midsole penetration protection | No |
| E Energy absorption in the heel area | Yes |
| M Instep protection | No |
| A Antistatic properties | Yes |
| AN Ankle protection | No |
| CR Cut resistant upper | No |
| SRA Antislip prop. on ceramic tile with SLS | Yes |
| SRB Antislip prop. on smooth steel with glycerol | Yes |
| SRC Antislip resistance SRA + SRB | Yes |
| Free-tex Membrane | Yes |
| Michelin Michelin® sole | No |
| BOA BOA Fit System | No |
| NON-METALIC Footwear without metal parts | No |
| ESD antistatic properties ESD | No |
| Winter Winter footwear | No |
| ANTICUT Anti-cut boots | No |
| Standard | 20347:2012 |
| Shoe marking | O2 |

Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 39 | 1,19 kg | 1,41 kg | 210 mm | 320 mm | 115 mm | 455 mm | 600 mm | 350 mm | 15,80 kg | 0,0 mm |
| 40 | 1,20 kg | 1,48 kg | 210 mm | 320 mm | 115 mm | 455 mm | 600 mm | 350 mm | 16,00 kg | 0,0 mm |
| 41 | 1,26 kg | 1,54 kg | 210 mm | 320 mm | 115 mm | 455 mm | 600 mm | 350 mm | 16,40 kg | 0,0 mm |
| 42 | 1,32 kg | 1,60 kg | 210 mm | 320 mm | 115 mm | 455 mm | 600 mm | 350 mm | 17,00 kg | 0,0 mm |
| 43 | 1,36 kg | 1,69 kg | 230 mm | 350 mm | 125 mm | 485 mm | 640 mm | 380 mm | 17,80 kg | 0,0 mm |
| 44 | 1,40 kg | 1,79 kg | 230 mm | 350 mm | 125 mm | 485 mm | 640 mm | 380 mm | 18,40 kg | 0,0 mm |
| 45 | 1,44 kg | 1,77 kg | 230 mm | 350 mm | 125 mm | 485 mm | 640 mm | 380 mm | 19,00 kg | 0,0 mm |
| 46 | 1,51 kg | 1,85 kg | 230 mm | 350 mm | 125 mm | 485 mm | 640 mm | 380 mm | 19,60 kg | 0,0 mm |
| 47 | 1,56 kg | 1,90 kg | 230 mm | 350 mm | 125 mm | 485 mm | 640 mm | 380 mm | 20,00 kg | 0,0 mm |

Business parameters

| | |
|---------------------|----------|
| Tarric | 64039993 |
| Country | CN |
| Weight | 1,53 kg |
| Add Unit | NPR |
| Add Quantity | 1 |