

# Technical sheet

## TAMPERE low cut safety shoes



Product code: 5625-S3



<b>upper</b>	polyamide abrasion resistant fabric PUTEK
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S3

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,97 kg	1,27 kg	205 mm	325 mm	115 mm	435 mm	600 mm	350 mm	14,00 kg	0,0 mm
37	1,07 kg	1,36 kg	205 mm	325 mm	115 mm	435 mm	600 mm	350 mm	14,40 kg	0,0 mm
38	1,08 kg	1,36 kg	205 mm	325 mm	115 mm	435 mm	600 mm	350 mm	14,60 kg	0,0 mm
39	1,10 kg	1,38 kg	205 mm	325 mm	115 mm	435 mm	600 mm	350 mm	15,20 kg	0,0 mm
40	1,13 kg	1,42 kg	205 mm	325 mm	115 mm	435 mm	600 mm	350 mm	15,90 kg	0,0 mm
41	1,20 kg	1,45 kg	205 mm	325 mm	115 mm	435 mm	600 mm	350 mm	16,40 kg	0,0 mm
42	1,21 kg	1,50 kg	205 mm	325 mm	115 mm	435 mm	600 mm	350 mm	16,50 kg	0,0 mm
43	1,26 kg	1,59 kg	215 mm	335 mm	125 mm	450 mm	625 mm	350 mm	16,80 kg	0,0 mm
44	1,28 kg	1,62 kg	215 mm	335 mm	125 mm	450 mm	625 mm	350 mm	17,40 kg	0,0 mm
45	1,37 kg	1,70 kg	215 mm	335 mm	125 mm	450 mm	625 mm	350 mm	18,20 kg	0,0 mm
46	1,40 kg	1,74 kg	215 mm	355 mm	130 mm	445 mm	645 mm	380 mm	18,80 kg	0,0 mm
47	1,40 kg	1,74 kg	215 mm	355 mm	130 mm	445 mm	645 mm	380 mm	19,20 kg	0,0 mm
48	1,43 kg	1,74 kg	215 mm	355 mm	130 mm	445 mm	645 mm	380 mm	19,40 kg	0,0 mm

## Business parameters

<b>Tarric</b>	64041990
<b>Country</b>	CN

<b>Weight</b>	1,50 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1