

Technical sheet

BUFFALO ankle occupational shoes

Product code: 7130-02



upper	cowhide leather CRAZY HORSE in a thickness 2,0 - 2,2 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	expanded polyurethane of high absorbency, antistatic
outsole	MICHELIN®-PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic
size	39 - 48
standard	EN ISO 20347:2012
version	O2 FO HRO SRC CI WR - without composite toe cap and kevlar midsole, hydrophobic, FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	Yes
WRU Water resistant upper	Yes
CI Insulation against cold	Yes
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	Yes
Michelin Michelin® sole	Yes
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	O2

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,44 kg	1,80 kg	270 mm	330 mm	125 mm	565 mm	645 mm	355 mm	19,20 kg	256,0 mm
40	1,44 kg	1,81 kg	270 mm	330 mm	125 mm	565 mm	645 mm	355 mm	19,00 kg	262,7 mm
41	1,47 kg	1,83 kg	270 mm	330 mm	125 mm	565 mm	645 mm	355 mm	19,60 kg	269,3 mm
42	1,50 kg	1,86 kg	270 mm	330 mm	125 mm	565 mm	645 mm	355 mm	19,80 kg	276,0 mm
43	1,54 kg	1,89 kg	270 mm	330 mm	125 mm	565 mm	645 mm	355 mm	20,20 kg	282,7 mm
44	1,65 kg	2,05 kg	280 mm	360 mm	130 mm	580 mm	670 mm	380 mm	21,80 kg	289,3 mm
45	1,67 kg	2,06 kg	280 mm	360 mm	130 mm	580 mm	670 mm	380 mm	22,00 kg	296,0 mm
46	1,74 kg	2,13 kg	280 mm	360 mm	130 mm	580 mm	670 mm	380 mm	23,00 kg	302,7 mm
47	1,83 kg	2,22 kg	280 mm	360 mm	130 mm	580 mm	670 mm	380 mm	23,40 kg	309,4 mm
48	1,98 kg	2,37 kg	280 mm	360 mm	130 mm	580 mm	670 mm	380 mm	25,00 kg	316,0 mm

Business parameters

Tarric	64039113
Country	CN
Weight	1,81 kg
Add Unit	NPR

Add Quantity 1