

Technical sheet

DORTMUND ankle safety shoes



Product code: 2540-S7LESD



upper	cowhide leather PULL-UP in a thickness of 2,0 - 2,2 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
size	39 - 48
standard	EN ISO 20345:2022, EN ISO 61340-5-1:2016
version	S7L FO HRO SR ESD - with composite toe cap and kevlar midsole, hydrophobic, MEMBRANE FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	Yes
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	Yes
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	Yes
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	Yes
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2023
Shoe marking	S7

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
40	1,55 kg	1,88 kg	260 mm	320 mm	120 mm	540 mm	600 mm	340 mm	19,80 kg	0,0 mm
41	1,62 kg	1,94 kg	260 mm	320 mm	120 mm	540 mm	600 mm	340 mm	20,20 kg	0,0 mm
42	1,66 kg	1,98 kg	260 mm	320 mm	120 mm	540 mm	600 mm	340 mm	20,60 kg	0,0 mm
43	1,67 kg	2,00 kg	265 mm	330 mm	125 mm	550 mm	630 mm	360 mm	21,20 kg	0,0 mm
44	1,76 kg	2,11 kg	275 mm	350 mm	125 mm	550 mm	630 mm	360 mm	21,80 kg	0,0 mm
45	1,83 kg	2,18 kg	275 mm	350 mm	125 mm	570 mm	650 mm	370 mm	22,80 kg	0,0 mm
46	1,88 kg	2,24 kg	275 mm	350 mm	125 mm	570 mm	650 mm	370 mm	23,40 kg	0,0 mm
47	1,93 kg	2,28 kg	275 mm	350 mm	125 mm	570 mm	650 mm	370 mm	24,00 kg	0,0 mm
48	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	1,71 kg
Add Unit	NPR

Add Quantity 1