

# Technical sheet

## LOSANGELES ankle safety shoes

Product code: 6440-S3



<b>upper</b>	cowhide leather coated, brushed in a thickness of 1,8 - 2,0 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	MICHELIN®-PU/RUBBER - up to 300°C, HRO, SRC, resistant to fuel oils, antislip, antistatic
<b>size</b>	37 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	Yes
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	No
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	Yes
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S3

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	1,44 kg	1,74 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	18,60 kg	246,6 mm
38	1,49 kg	1,79 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	19,00 kg	253,3 mm
39	1,57 kg	1,86 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	19,80 kg	260,0 mm
40	1,62 kg	1,92 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	20,20 kg	266,7 mm
41	1,65 kg	1,95 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	20,80 kg	273,3 mm
42	1,68 kg	1,97 kg	260 mm	320 mm	115 mm	545 mm	595 mm	350 mm	21,20 kg	280,0 mm
43	1,78 kg	2,14 kg	275 mm	350 mm	125 mm	560 mm	650 mm	370 mm	22,60 kg	286,7 mm
44	1,83 kg	2,19 kg	275 mm	350 mm	125 mm	560 mm	650 mm	370 mm	23,40 kg	293,3 mm
45	1,92 kg	2,28 kg	275 mm	350 mm	125 mm	560 mm	650 mm	370 mm	24,00 kg	300,0 mm
46	2,00 kg	2,36 kg	275 mm	350 mm	125 mm	560 mm	650 mm	370 mm	24,80 kg	306,7 mm
47	2,06 kg	2,42 kg	275 mm	350 mm	125 mm	560 mm	650 mm	370 mm	25,60 kg	313,4 mm
48	2,06 kg	2,45 kg	275 mm	350 mm	125 mm	560 mm	650 mm	370 mm	25,80 kg	320,1 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN

<b>Weight</b>	1,50 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1