

# Technical sheet

## MADRID ankle occupational shoes

Product code: 2990-01



<b>upper</b>	brushed cowhide suede leather VELOUR in a thickness of 1,7 - 1,9 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	anatomically shaped from material EVA with a high absorbency, antistatic
<b>outsole</b>	PU/PU - transparent, resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	O1 FO SRC - without steel toe cap

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2012
<b>Shoe marking</b>	O1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,03 kg	1,31 kg	225 mm	310 mm	120 mm	475 mm	610 mm	340 mm	14,20 kg	244,0 mm
37	1,06 kg	1,31 kg	225 mm	310 mm	120 mm	475 mm	610 mm	340 mm	14,50 kg	251,0 mm
38	1,08 kg	1,33 kg	225 mm	310 mm	120 mm	475 mm	610 mm	340 mm	14,70 kg	259,0 mm
39	1,12 kg	1,37 kg	225 mm	310 mm	120 mm	475 mm	610 mm	340 mm	15,10 kg	266,0 mm
40	1,16 kg	1,45 kg	225 mm	310 mm	120 mm	475 mm	610 mm	340 mm	16,00 kg	272,0 mm
41	1,20 kg	1,49 kg	225 mm	310 mm	120 mm	475 mm	610 mm	340 mm	16,20 kg	279,0 mm
42	1,34 kg	1,62 kg	225 mm	310 mm	120 mm	475 mm	610 mm	340 mm	17,40 kg	286,0 mm
43	1,39 kg	1,70 kg	330 mm	235 mm	120 mm	490 mm	635 mm	370 mm	18,40 kg	293,0 mm
44	1,41 kg	1,71 kg	330 mm	235 mm	120 mm	490 mm	635 mm	370 mm	18,60 kg	299,0 mm
45	1,44 kg	1,75 kg	330 mm	235 mm	120 mm	490 mm	635 mm	370 mm	19,20 kg	305,0 mm
46	1,47 kg	1,78 kg	355 mm	240 mm	125 mm	480 mm	640 mm	370 mm	20,00 kg	314,0 mm
47	1,49 kg	1,80 kg	355 mm	240 mm	125 mm	480 mm	640 mm	370 mm	20,60 kg	320,0 mm
48	1,52 kg	1,83 kg	355 mm	240 mm	125 mm	480 mm	640 mm	370 mm	21,00 kg	327,0 mm

## Business parameters

<b>Tarric</b>	64039113
<b>Country</b>	CN

<b>Weight</b>	1,55 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1