

Technical sheet

NOTTINGHAM occupational boots



Product code: 6570-02



upper	abrasion resistant textile material OXFORD
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	expanded polyurethane of high absorbency, antistatic
outsole	EVA/RUBBER - antistatic, glued construction
size	39 - 47
standard	EN ISO 20347:2012
version	O2 WR CI SRA - without composite toe cap and kevlar midsole, hydrophobic, FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	Yes
WRU Water resistant upper	Yes
CI Insulation against cold	Yes
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	No
P Midsole penetration protection	No
E Energy absorption in the heel area	No
M Instep protection	No
A Antistatic properties	No
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	Yes
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	O2

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,01 kg	1,36 kg	310 mm	330 mm	120 mm	620 mm	635 mm	355 mm	14,80 kg	0,0 mm
37	1,03 kg	1,39 kg	310 mm	330 mm	120 mm	620 mm	635 mm	355 mm	15,00 kg	0,0 mm
38	1,09 kg	1,44 kg	310 mm	330 mm	120 mm	620 mm	635 mm	355 mm	15,20 kg	0,0 mm
39	1,18 kg	1,54 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	16,80 kg	0,0 mm
40	1,20 kg	1,56 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	17,20 kg	0,0 mm
41	1,25 kg	1,61 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	17,40 kg	0,0 mm
42	1,31 kg	1,67 kg	310 mm	335 mm	125 mm	630 mm	640 mm	360 mm	18,00 kg	0,0 mm
43	1,35 kg	1,77 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	19,60 kg	0,0 mm
44	1,40 kg	1,82 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	19,80 kg	0,0 mm
45	1,44 kg	1,86 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	20,20 kg	0,0 mm
46	1,48 kg	1,90 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	20,60 kg	0,0 mm
47	1,55 kg	1,97 kg	330 mm	365 mm	135 mm	685 mm	710 mm	390 mm	21,40 kg	0,0 mm

Business parameters

Tarric	64041990
Country	CN

Weight	1,50 kg
Add Unit	NPR
Add Quantity	1