

# Technical sheet

## FUKUOKA occupational boots

Product code: 1005-04



<b>upper</b>	PVC/NITRIL - acid-resistant
<b>outsole</b>	PVC/NITRIL - acid-resistant
<b>size</b>	37 - 48
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	04 SRA - without steel toe cap

### Properties

**PL** Midsole penetration protection nonmetallic - PL    No

<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Shoe marking</b>	O4

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	1,85 kg	1,85 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	19,74 kg	0,0 mm
38	1,83 kg	1,83 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	19,49 kg	0,0 mm
39	1,90 kg	1,90 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	20,22 kg	0,0 mm
40	1,93 kg	1,93 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	20,45 kg	0,0 mm
41	2,01 kg	2,01 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	21,30 kg	0,0 mm
42	2,09 kg	2,09 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	22,06 kg	0,0 mm
43	2,17 kg	2,17 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	22,87 kg	0,0 mm
44	2,30 kg	2,30 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	24,17 kg	0,0 mm
45	2,29 kg	2,29 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	24,12 kg	0,0 mm
46	2,40 kg	2,40 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	25,22 kg	0,0 mm
47	2,48 kg	2,48 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	26,00 kg	0,0 mm
48	2,51 kg	2,51 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	27,00 kg	0,0 mm

## Business parameters

<b>Tarric</b>	64019290
<b>Country</b>	CN
<b>Weight</b>	2,15 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1