

# Technical sheet

## LOUISIANA low cut safety shoes BOA

Product code: 6335-S1P



<b>upper</b>	breathable abrasion resistant textile with TPU print
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyuretane foam coated with fabric MESH, antistatic
<b>outsole</b>	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
<b>size</b>	39 - 47
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1P SRC - with composite toe cap and kevlar midsole

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	Yes
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,04 kg	1,32 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	14,00 kg	257,0 mm
40	1,11 kg	1,39 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	14,60 kg	263,7 mm
41	1,12 kg	1,39 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	14,80 kg	270,3 mm
42	1,18 kg	1,46 kg	210 mm	320 mm	115 mm	440 mm	600 mm	350 mm	15,60 kg	277,0 mm
43	1,26 kg	1,58 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	16,60 kg	283,7 mm
44	1,28 kg	1,60 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	16,80 kg	290,3 mm
45	1,30 kg	1,62 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	17,20 kg	297,0 mm
46	1,38 kg	1,69 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	17,80 kg	303,7 mm
47	1,40 kg	1,72 kg	230 mm	350 mm	125 mm	465 mm	640 mm	375 mm	18,20 kg	310,3 mm

## Business parameters

<b>Tarric</b>	64041990
<b>Country</b>	CN
<b>Weight</b>	1,50 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1