

# Technical sheet

## BALTIMORE ankle safety shoes

Product code: 4980-S3



<b>upper</b>	cowhide leather CRAZY HORSE in a thickness of 1,7 - 1,9 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	MICHELIN® EVA/RUBBER - resistant to fuel oils, antistatic, antislip
<b>size</b>	40 - 47
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S3 SRC - with composite toe cap and kevlar midsole, hydrophobic

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	Yes
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S3

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
40	1,58 kg	1,95 kg	295 mm	330 mm	130 mm	610 mm	650 mm	350 mm	20,80 kg	269,0 mm
41	1,63 kg	1,99 kg	295 mm	330 mm	130 mm	610 mm	650 mm	350 mm	21,20 kg	277,0 mm
42	1,67 kg	2,01 kg	295 mm	330 mm	130 mm	610 mm	650 mm	350 mm	21,60 kg	282,0 mm
43	1,81 kg	2,15 kg	295 mm	330 mm	130 mm	610 mm	650 mm	350 mm	23,30 kg	290,0 mm
44	1,85 kg	2,22 kg	310 mm	350 mm	135 mm	640 mm	675 mm	370 mm	24,20 kg	299,0 mm
45	1,90 kg	2,37 kg	310 mm	350 mm	135 mm	640 mm	675 mm	370 mm	25,60 kg	307,0 mm
46	2,01 kg	2,40 kg	310 mm	350 mm	135 mm	640 mm	675 mm	370 mm	26,00 kg	315,0 mm
47	2,10 kg	2,48 kg	310 mm	350 mm	135 mm	640 mm	675 mm	370 mm	27,00 kg	323,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN
<b>Weight</b>	1,83 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1