

Technical sheet

EDINBURGH high heel safety shoes

Product code: 5180-S3



upper	cowhide leather CRAZY HORSE in a thickness of 1,9 - 2,1 mm
lining	hair plush DELTA
inner insole	anatomically shaped, coated with hair plush DELTA, antistatic
outsole	PU/PU - resistant to fuel oils, antislip, antistatic, double density injection
size	39 - 48
standard	EN ISO 20345:2011
version	S3 SRC CI - with plastic toe cap and kevlar midsole, hydrophobic, winter design

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	Yes
CI Insulation against cold	Yes
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	Yes
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,45 kg	1,86 kg	320 mm	350 mm	125 mm	650 mm	650 mm	380 mm	20,20 kg	252,0 mm
40	1,48 kg	1,89 kg	320 mm	350 mm	125 mm	650 mm	650 mm	380 mm	20,40 kg	259,5 mm
41	1,58 kg	1,99 kg	320 mm	350 mm	125 mm	650 mm	650 mm	380 mm	21,20 kg	267,0 mm
42	1,62 kg	2,03 kg	320 mm	350 mm	125 mm	650 mm	650 mm	380 mm	21,80 kg	274,5 mm
43	1,68 kg	2,15 kg	380 mm	355 mm	130 mm	665 mm	740 mm	400 mm	23,20 kg	282,0 mm
44	1,75 kg	2,21 kg	380 mm	355 mm	130 mm	665 mm	740 mm	400 mm	24,00 kg	289,5 mm
45	1,78 kg	2,25 kg	380 mm	355 mm	130 mm	665 mm	740 mm	400 mm	24,20 kg	297,0 mm
46	1,86 kg	2,32 kg	380 mm	355 mm	130 mm	665 mm	740 mm	400 mm	25,00 kg	304,5 mm
47	1,91 kg	2,37 kg	380 mm	355 mm	130 mm	665 mm	740 mm	400 mm	25,60 kg	312,0 mm
48	1,94 kg	2,41 kg	380 mm	355 mm	130 mm	665 mm	740 mm	400 mm	25,80 kg	319,5 mm

Business parameters

Tarric	64034000
Country	CN
Weight	2,24 kg
Add Unit	NPR

Add Quantity 1