

Technical sheet

LONDON high heel safety shoes

Product code: 2330-S3



upper	cowhide leather in a thickness of 2,0 - 2,2 mm
lining	thermo-insulation fabric 3M THINSULATE
inner insole	HI-POLY - anatomically formed, coated with CAMBRELLA, antistatic
outsole	PU/TPU - resistant to fuel oils, antistatic, antislip, double density injection
size	37 - 49
standard	EN ISO 20345:2011
version	S3 CI SRC - with steel toe cap and midsole, hydrophobic

Properties

PL Midsole penetration protection nonmetalic - PL	No
PS Midsole penetration protection nonmetalic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	No
WRU Water resistant upper	Yes
CI Insulation against cold	Yes
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	Yes
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	1,65 kg	2,01 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	21,40 kg	237,0 mm
38	1,67 kg	2,03 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	21,80 kg	244,5 mm
39	1,73 kg	2,09 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	22,20 kg	252,0 mm
40	1,79 kg	2,15 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	22,60 kg	259,5 mm
41	1,79 kg	2,15 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	23,00 kg	267,0 mm
42	1,91 kg	2,27 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	24,00 kg	274,5 mm
43	1,94 kg	2,35 kg	350 mm	330 mm	125 mm	645 mm	680 mm	375 mm	25,20 kg	282,0 mm
44	2,04 kg	2,44 kg	350 mm	330 mm	125 mm	645 mm	680 mm	375 mm	26,20 kg	289,5 mm
45	2,14 kg	2,57 kg	350 mm	330 mm	125 mm	645 mm	680 mm	375 mm	26,60 kg	297,0 mm
46	2,17 kg	2,62 kg	350 mm	330 mm	125 mm	645 mm	680 mm	375 mm	27,00 kg	304,5 mm
47	2,28 kg	2,69 kg	350 mm	330 mm	125 mm	645 mm	680 mm	375 mm	28,60 kg	312,0 mm
48	2,39 kg	2,78 kg	350 mm	330 mm	125 mm	645 mm	680 mm	375 mm	29,50 kg	319,5 mm
49	2,48 kg	2,89 kg	350 mm	330 mm	125 mm	645 mm	680 mm	375 mm	30,70 kg	327,0 mm

Business parameters

Tarric	64034000
Country	CN

Weight	2,24 kg
Add Unit	NPR
Add Quantity	1