

Technical sheet

SAPPORO safety boots

Product code: 1002-S5



upper	PVC/NITRIL - acid-resistant
outsole	PVC/NITRIL - acid-resistant
size	37 - 48
standard	EN ISO 20345:2011
version	S5 SRA - with steel toe cap and midsole

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No

SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S5

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	2,02 kg	2,02 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	21,26 kg	0,0 mm
38	2,05 kg	2,05 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	21,56 kg	0,0 mm
39	2,18 kg	2,18 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	22,86 kg	0,0 mm
40	2,18 kg	2,18 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	22,92 kg	0,0 mm
41	2,25 kg	2,25 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	23,58 kg	0,0 mm
42	2,32 kg	2,32 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	24,26 kg	0,0 mm
43	2,43 kg	2,43 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	25,44 kg	0,0 mm
44	2,55 kg	2,55 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	26,56 kg	0,0 mm
45	2,59 kg	2,59 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	27,00 kg	0,0 mm
46	2,65 kg	2,65 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	27,56 kg	0,0 mm
47	2,82 kg	2,82 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	29,28 kg	0,0 mm
48	2,96 kg	2,96 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	30,00 kg	0,0 mm

Business parameters

Tarric	64011000
Country	CN
Weight	2,40 kg
Add Unit	NPR
Add Quantity	1