






FA 60 029 XX

P. 1 | 2



HS CODE
63079098
CARTON SIZE / PCS.
FA 60 029 05 : 40 x 40 x 24 cm / 10
FA 60 029 10 : 60 x 40 x 24 cm / 20
AET (UE) N°2777/11681-01/E00-00
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 60 029 05 FA 60 029 10
CE	EN 795:2012 Type B
	x1
LG.	Max. 5 m Max. 10 m
MAT.	 45 mm PES
R (kN) / MBS (kN)	18 kN / 19 kN
	0.61 kg 0.98 kg



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)