

Technical sheet

HAVANA low cut occupational shoes

Product code: 4315-02



upper	cowhide leather NUBUCK in a thickness of 1,9 - 2,1 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
size	36 - 49
standard	EN ISO 20347:2012
version	OB E WRU - without steel toe cap, hydrophobic, FREE-TEX®

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	Yes
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	OB

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,04 kg	1,29 kg	230 mm	335 mm	120 mm	490 mm	630 mm	350 mm	14,30 kg	0,0 mm
37	1,04 kg	1,31 kg	230 mm	335 mm	120 mm	490 mm	630 mm	350 mm	14,40 kg	0,0 mm
38	1,07 kg	1,35 kg	230 mm	335 mm	120 mm	490 mm	630 mm	350 mm	14,50 kg	0,0 mm
39	1,09 kg	1,37 kg	230 mm	335 mm	120 mm	490 mm	630 mm	350 mm	14,70 kg	0,0 mm
40	1,11 kg	1,40 kg	230 mm	335 mm	120 mm	490 mm	630 mm	350 mm	14,90 kg	0,0 mm
41	1,13 kg	1,43 kg	230 mm	335 mm	120 mm	490 mm	630 mm	350 mm	15,10 kg	0,0 mm
42	1,18 kg	1,48 kg	255 mm	350 mm	125 mm	540 mm	650 mm	375 mm	16,20 kg	0,0 mm
43	1,21 kg	1,51 kg	255 mm	350 mm	125 mm	540 mm	650 mm	375 mm	16,40 kg	0,0 mm
44	1,26 kg	1,57 kg	255 mm	350 mm	125 mm	540 mm	650 mm	375 mm	16,80 kg	0,0 mm
45	1,32 kg	1,62 kg	255 mm	350 mm	125 mm	540 mm	650 mm	375 mm	17,40 kg	0,0 mm
46	1,35 kg	1,68 kg	260 mm	370 mm	130 mm	550 mm	670 mm	400 mm	18,20 kg	0,0 mm
47	1,39 kg	1,73 kg	260 mm	370 mm	130 mm	550 mm	670 mm	400 mm	18,40 kg	0,0 mm
48	1,43 kg	1,79 kg	260 mm	370 mm	130 mm	550 mm	670 mm	400 mm	18,60 kg	0,0 mm
49	1,44 kg	1,80 kg	260 mm	370 mm	130 mm	550 mm	670 mm	400 mm	18,80 kg	0,0 mm

Business parameters

Tarric 64039993

Country	CN
Weight	1,50 kg
Add Unit	NPR
Add Quantity	1