

# Technical sheet

## IOWA low cut safety shoes

Product code: 4745-S1P



<b>upper</b>	brushed cow suede leather VELOUR in a combination with textile in a thickness of 1,5 - 1,7 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	EVA/RUBBER - glued construction
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1P SRA - with plastic toe cap and kevlar midsole

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,94 kg	1,25 kg	210 mm	320 mm	115 mm	450 mm	630 mm	340 mm	14,20 kg	236,0 mm
37	0,99 kg	1,30 kg	210 mm	320 mm	115 mm	450 mm	630 mm	340 mm	14,60 kg	243,0 mm
38	1,05 kg	1,36 kg	210 mm	320 mm	115 mm	450 mm	630 mm	340 mm	15,20 kg	250,0 mm
39	1,09 kg	1,40 kg	210 mm	320 mm	115 mm	450 mm	630 mm	340 mm	15,40 kg	257,0 mm
40	1,12 kg	1,47 kg	230 mm	320 mm	120 mm	500 mm	630 mm	340 mm	16,20 kg	263,0 mm
41	1,19 kg	1,53 kg	230 mm	320 mm	120 mm	500 mm	630 mm	340 mm	16,80 kg	270,0 mm
42	1,21 kg	1,58 kg	250 mm	340 mm	130 mm	540 mm	680 mm	360 mm	17,80 kg	276,0 mm
43	1,27 kg	1,64 kg	250 mm	340 mm	130 mm	540 mm	680 mm	360 mm	18,20 kg	283,0 mm
44	1,34 kg	1,71 kg	250 mm	340 mm	130 mm	540 mm	680 mm	360 mm	18,80 kg	289,0 mm
45	1,38 kg	1,78 kg	270 mm	370 mm	130 mm	570 mm	680 mm	400 mm	19,80 kg	296,0 mm
46	1,41 kg	1,82 kg	270 mm	370 mm	130 mm	570 mm	680 mm	400 mm	20,20 kg	303,0 mm
47	1,45 kg	1,86 kg	270 mm	370 mm	130 mm	580 mm	685 mm	400 mm	20,60 kg	310,0 mm
48	1,48 kg	1,89 kg	270 mm	370 mm	130 mm	580 mm	685 mm	400 mm	21,00 kg	316,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	BD

<b>Weight</b>	1,45 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1