

# Technical sheet

## PHILADELPHIA low cut outdoor shoes BOA

Product code: 4355-60



<b>upper</b>	breathable, abrasion-resistant textile with CPU printing
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	anatomically shaped from material EVA with a high absorbency, antistatic
<b>outsole</b>	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
<b>size</b>	39 - 47
<b>usability</b>	shoes suitable for daily wear and light outdoor activities
<b>version</b>	black/yellow colour, with Boa® Closure System

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	No
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	No
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	No
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	No
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	Yes
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
38	0,61 kg	0,90 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	10,00 kg	250,4 mm
39	0,63 kg	0,92 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	10,20 kg	257,0 mm
40	0,65 kg	0,93 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	10,40 kg	263,7 mm
41	0,68 kg	0,97 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	10,60 kg	270,3 mm
42	0,70 kg	0,98 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	10,80 kg	277,0 mm
43	0,72 kg	1,06 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	11,80 kg	283,7 mm
44	0,77 kg	1,10 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	12,00 kg	290,3 mm
45	0,80 kg	1,11 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	12,40 kg	297,0 mm
46	0,81 kg	1,14 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	12,60 kg	303,6 mm
47	0,83 kg	1,19 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	13,00 kg	310,3 mm

## Business parameters

<b>Tarric</b>	64041990
<b>Country</b>	CN
<b>Weight</b>	0,96 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1