

# Technical sheet

## WINNIPEG ankle outdoor shoes



Product code: 4900-40



<b>upper</b>	cowhide leather PULL-UP in a thickness of 1,7 - 1,9 mm
<b>lining</b>	breathable thermo-insulation MEMBRANE FREE-TEX®
<b>inner insole</b>	expanded polyurethane of high absorbency, antistatic
<b>outsole</b>	EVA/RUBBER - glued constriction
<b>size</b>	40 - 47
<b>usability</b>	shoes suitable for daily wear and outdoor activities
<b>version</b>	brown colour, FREE-TEX®

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	No
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	No
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	No
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	No
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
40	1,37 kg	1,75 kg	290 mm	330 mm	125 mm	600 mm	650 mm	345 mm	19,00 kg	269,0 mm
41	1,39 kg	1,77 kg	290 mm	330 mm	125 mm	600 mm	650 mm	345 mm	19,40 kg	277,0 mm
42	1,45 kg	1,83 kg	290 mm	330 mm	125 mm	600 mm	650 mm	345 mm	20,00 kg	282,0 mm
43	1,53 kg	1,90 kg	290 mm	330 mm	125 mm	600 mm	650 mm	345 mm	20,60 kg	290,0 mm
44	1,56 kg	1,99 kg	310 mm	360 mm	130 mm	640 mm	680 mm	390 mm	21,80 kg	299,0 mm
45	1,66 kg	2,10 kg	310 mm	360 mm	130 mm	640 mm	680 mm	390 mm	23,20 kg	307,0 mm
46	1,74 kg	2,17 kg	310 mm	360 mm	130 mm	640 mm	680 mm	390 mm	23,40 kg	315,0 mm
47	1,79 kg	2,22 kg	310 mm	360 mm	130 mm	640 mm	680 mm	390 mm	24,80 kg	323,0 mm

## Business parameters

<b>Tarric</b>	64039113
<b>Country</b>	CN
<b>Weight</b>	1,90 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1