

# Technical sheet

## LIMA low cut occupational shoes

Product code: 4115-02



<b>upper</b>	cowhide leather NUBUCK in a thickness of 1,9 - 2,1 mm
<b>lining</b>	breathable thermo-insulation MEMBRANE FREE-TEX®
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	EVA/RUBBER - antistatic, antislip, glued construction
<b>size</b>	36 - 49
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	OB E WRU SRA - without steel toe cap, hydrophobic, FREE-TEX®

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	No
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	No
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	Yes
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2012
<b>Shoe marking</b>	OB

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,92 kg	1,20 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,20 kg	0,0 mm
37	0,94 kg	1,22 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,40 kg	0,0 mm
38	0,96 kg	1,25 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,60 kg	0,0 mm
39	1,03 kg	1,31 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	13,90 kg	0,0 mm
40	1,06 kg	1,34 kg	230 mm	330 mm	120 mm	490 mm	630 mm	350 mm	14,40 kg	0,0 mm
41	1,07 kg	1,40 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	15,20 kg	0,0 mm
42	1,18 kg	1,49 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	16,00 kg	0,0 mm
43	1,20 kg	1,52 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	16,60 kg	0,0 mm
44	1,24 kg	1,56 kg	255 mm	350 mm	125 mm	535 mm	640 mm	370 mm	17,00 kg	0,0 mm
45	1,28 kg	1,61 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	17,40 kg	0,0 mm
46	1,34 kg	1,68 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	18,00 kg	0,0 mm
47	1,40 kg	1,74 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	18,60 kg	0,0 mm
48	1,41 kg	1,75 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	18,80 kg	0,0 mm
49	1,50 kg	1,84 kg	260 mm	370 mm	130 mm	545 mm	670 mm	395 mm	20,00 kg	0,0 mm

## Business parameters

**Tarric** 64039993

<b>Country</b>	CN
<b>Weight</b>	1,43 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1