

Technical sheet

MISSISSIPPI low cut safety shoes

Product code: 4755-S1P



| | |
|---------------------|--|
| upper | brushed cow suede leather VELOUR in a combination with textile in a thickness of 1,2 - 1,4 mm |
| lining | laminated breathable fabric MESH |
| inner insole | HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic |
| outsole | EVA/RUBBER - glued construction |
| size | 36 - 48 |
| standard | EN ISO 20345:2011 |
| version | S1P SRA - with plastic toe cap and kevlar midsole |

Properties

| | |
|---|------------|
| PL Midsole penetration protection nonmetallic - PL | No |
| PS Midsole penetration protection nonmetallic - PS | No |
| SR Antislip prop. on ceramic with glycerol | No |
| WPA Water resistant upper | No |
| HRO Resist. of the outsole against contact heat | No |
| WR Water resistant | No |
| WRU Water resistant upper | No |
| CI Insulation against cold | No |
| HI Insulation of the outsole against heat | No |
| FO Resist. of the outsole against fuel oils | Yes |
| P Midsole penetration protection | Yes |
| E Energy absorption in the heel area | Yes |
| M Instep protection | No |
| A Antistatic properties | Yes |
| AN Ankle protection | No |
| CR Cut resistant upper | No |
| SRA Antislip prop. on ceramic tile with SLS | Yes |
| SRB Antislip prop. on smooth steel with glycerol | No |
| SRC Antislip resistance SRA + SRB | No |
| Free-tex Membrane | No |
| Michelin Michelin® sole | No |
| BOA BOA Fit System | No |
| NON-METALIC Footwear without metal parts | No |
| ESD antistatic properties ESD | No |
| Winter Winter footwear | No |
| ANTICUT Anti-cut boots | No |
| Standard | 20345:2012 |
| Shoe marking | S1 |

Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36 | 0,94 kg | 1,25 kg | 210 mm | 320 mm | 115 mm | 450 mm | 630 mm | 340 mm | 14,20 kg | 236,0 mm |
| 37 | 0,99 kg | 1,30 kg | 210 mm | 320 mm | 115 mm | 450 mm | 630 mm | 340 mm | 14,60 kg | 243,0 mm |
| 38 | 1,05 kg | 1,36 kg | 210 mm | 320 mm | 115 mm | 450 mm | 630 mm | 340 mm | 15,20 kg | 250,0 mm |
| 39 | 1,09 kg | 1,40 kg | 210 mm | 320 mm | 115 mm | 450 mm | 630 mm | 340 mm | 15,40 kg | 257,0 mm |
| 40 | 1,12 kg | 1,47 kg | 230 mm | 320 mm | 120 mm | 500 mm | 630 mm | 340 mm | 16,20 kg | 263,0 mm |
| 41 | 1,19 kg | 1,53 kg | 230 mm | 320 mm | 120 mm | 500 mm | 630 mm | 340 mm | 16,80 kg | 270,0 mm |
| 42 | 1,21 kg | 1,58 kg | 250 mm | 340 mm | 130 mm | 540 mm | 680 mm | 360 mm | 17,80 kg | 276,0 mm |
| 43 | 1,27 kg | 1,64 kg | 250 mm | 340 mm | 130 mm | 540 mm | 680 mm | 360 mm | 18,20 kg | 283,0 mm |
| 44 | 1,34 kg | 1,71 kg | 250 mm | 340 mm | 130 mm | 540 mm | 680 mm | 360 mm | 18,80 kg | 289,0 mm |
| 45 | 1,38 kg | 1,78 kg | 270 mm | 370 mm | 130 mm | 570 mm | 680 mm | 400 mm | 19,80 kg | 296,0 mm |
| 46 | 1,41 kg | 1,82 kg | 270 mm | 370 mm | 130 mm | 570 mm | 680 mm | 400 mm | 20,20 kg | 303,0 mm |
| 47 | 1,45 kg | 1,86 kg | 270 mm | 370 mm | 130 mm | 580 mm | 685 mm | 400 mm | 20,60 kg | 310,0 mm |
| 48 | 1,48 kg | 1,89 kg | 270 mm | 370 mm | 130 mm | 580 mm | 685 mm | 400 mm | 21,00 kg | 316,0 mm |

Business parameters

| | |
|----------------|----------|
| Tarric | 64034000 |
| Country | BD |

Weight 1,45 kg
Add Unit NPR
Add Quantity 1