

# Technical sheet

## BELFAST safety boots, ANTICUT

Product code: 2350-S3



<b>upper</b>	cowhide leather in a thickness of 2,0 - 2,2 mm
<b>lining</b>	laminated breathable fabric CAMBRELLA
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	39 - 47

<b>standard</b>	EN ISO 20345:2011	EN ISO 17249:2013/AC:2014-02
<b>version</b>	S3 HRO SRC CI ANTICUT LEVEL 1 – with steel toe cap and midsole, hydrophobic, anticut kevlar lining, kevlar sewing	

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	Yes
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	Yes
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	Yes
<b>ANTICUT</b> Anti-cut boots	Yes
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S3

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	2,14 kg	2,57 kg	330 mm	390 mm	125 mm	650 mm	680 mm	420 mm	27,40 kg	252,0 mm
40	2,16 kg	2,59 kg	330 mm	390 mm	125 mm	650 mm	680 mm	420 mm	27,60 kg	259,5 mm
41	2,22 kg	2,65 kg	330 mm	390 mm	125 mm	650 mm	680 mm	420 mm	28,20 kg	267,0 mm
42	2,31 kg	2,75 kg	330 mm	390 mm	125 mm	650 mm	680 mm	420 mm	28,80 kg	274,5 mm
43	2,41 kg	2,92 kg	350 mm	420 mm	135 mm	700 mm	720 mm	450 mm	31,00 kg	282,0 mm
44	2,45 kg	2,96 kg	350 mm	420 mm	135 mm	700 mm	720 mm	450 mm	31,40 kg	289,5 mm
45	2,57 kg	3,08 kg	350 mm	420 mm	135 mm	700 mm	720 mm	450 mm	32,80 kg	297,0 mm
46	2,60 kg	3,10 kg	350 mm	420 mm	135 mm	700 mm	720 mm	450 mm	33,60 kg	304,5 mm
47	2,77 kg	3,26 kg	350 mm	420 mm	135 mm	700 mm	720 mm	450 mm	34,40 kg	312,0 mm

## **Business parameters**

<b>Tarric</b>	64034000
<b>Country</b>	CN
<b>Weight</b>	2,60 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1