

# Technical sheet

## MILWAUKEE low cut safety shoes



Product code: 8185-S3ESD



<b>upper</b>	polyamide abrasion resistant fabric PUTEK
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	MICHELIN®-PU/RUBBER - resistant to fuel oils, antistatic, antislip
<b>size</b>	36 - 47
<b>standard</b>	EN ISO 20345:2011, EN ISO 61340-5-1:2016
<b>version</b>	S3 ESD SRC - with composite toe cap and kevlar midsole - antistatic properties ESD, NON METALLIC

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	Yes
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S3

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,92 kg	1,18 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	12,20 kg	233,0 mm
37	0,93 kg	1,19 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	12,40 kg	240,0 mm
38	0,97 kg	1,24 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	12,80 kg	247,0 mm
39	1,01 kg	1,27 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	13,40 kg	254,0 mm
40	1,04 kg	1,31 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	13,80 kg	261,0 mm
41	0,08 kg	1,35 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	14,20 kg	268,0 mm
42	1,13 kg	1,40 kg	200 mm	315 mm	120 mm	425 mm	620 mm	330 mm	14,60 kg	275,0 mm
43	1,19 kg	1,48 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	15,60 kg	282,0 mm
44	1,24 kg	1,54 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	16,20 kg	289,0 mm
45	1,28 kg	1,56 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	16,40 kg	296,0 mm
46	1,33 kg	1,63 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	17,00 kg	303,0 mm
47	1,38 kg	1,68 kg	210 mm	345 mm	125 mm	445 mm	650 mm	360 mm	17,40 kg	310,0 mm

## Business parameters

<b>Tarric</b>	64041990
<b>Country</b>	CN

**Weight** 1,50 kg  
**Add Unit** NPR  
**Add Quantity** 1