

# Technical sheet

## NASHVILLE low cut safety shoes



Product code: 4345-S1



<b>upper</b>	breathable, abrasion-resistant textile with CPU printing
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	anatomically shaped from material EVA with a high absorbency, antistatic
<b>outsole</b>	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
<b>size</b>	39 - 47
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1 SRA - with composite toe cap

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	0,80 kg	1,08 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	11,60 kg	257,0 mm
40	0,87 kg	1,15 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	12,40 kg	263,7 mm
41	0,89 kg	1,17 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	12,60 kg	270,3 mm
42	0,94 kg	1,22 kg	210 mm	320 mm	115 mm	440 mm	595 mm	340 mm	12,80 kg	277,0 mm
43	1,00 kg	1,32 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	14,20 kg	283,7 mm
44	1,01 kg	1,33 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	14,40 kg	290,3 mm
45	1,05 kg	1,37 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	14,80 kg	297,0 mm
46	1,09 kg	1,41 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	15,20 kg	303,6 mm
47	1,13 kg	1,45 kg	225 mm	350 mm	125 mm	475 mm	640 mm	375 mm	15,60 kg	310,3 mm

## Business parameters

<b>Tarric</b>	64041990
<b>Country</b>	CN
<b>Weight</b>	1,12 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1