

# Technical sheet

## VIRGINIA low cut occupational shoes

Product code: 4375-02



|                     |   |
|---------------------|---|
| <b>upper</b>        | cowhide leather NUBUCK in a thickness of 1,9 - 2,1 mm   |
| <b>lining</b>       | breathable thermo-insulation MEMBRANE FREE-TEX®   |
| <b>inner insole</b> | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic |
| <b>outsole</b>      | MICHELIN EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction          |
| <b>size</b>         | 38 - 47   |
| <b>standard</b>     | EN ISO 20347:2012   |
| <b>version</b>      | O2 FO SRA - without steel toe cap, hydrophobic, FREE-TEX®                                       |

## Properties

|   |            |
|---|------------|
| <b>PL</b> Midsole penetration protection nonmetallic - PL | No         |
| <b>PS</b> Midsole penetration protection nonmetallic - PS | No         |
| <b>SR</b> Antislip prop. on ceramic with glycerol         | No         |
| <b>WPA</b> Water resistant upper                          | No         |
| <b>HRO</b> Resist. of the outsole against contact heat    | No         |
| <b>WR</b> Water resistant                                 | No         |
| <b>WRU</b> Water resistant upper                          | No         |
| <b>CI</b> Insulation against cold                         | No         |
| <b>HI</b> Insulation of the outsole against heat          | No         |
| <b>FO</b> Resist. of the outsole against fuel oils        | Yes        |
| <b>P</b> Midsole penetration protection                   | No         |
| <b>E</b> Energy absorption in the heel area               | Yes        |
| <b>M</b> Instep protection                                | No         |
| <b>A</b> Antistatic properties                            | Yes        |
| <b>AN</b> Ankle protection                                | No         |
| <b>CR</b> Cut resistant upper                             | No         |
| <b>SRA</b> Antislip prop. on ceramic tile with SLS        | Yes        |
| <b>SRB</b> Antislip prop. on smooth steel with glycerol   | Yes        |
| <b>SRC</b> Antislip resistance SRA + SRB                  | Yes        |
| <b>Free-tex</b> Membrane                                  | Yes        |
| <b>Michelin</b> Michelin® sole                            | Yes        |
| <b>BOA</b> BOA Fit System                                 | No         |
| <b>NON-METALIC</b> Footwear without metal parts           | No         |
| <b>ESD</b> antistatic properties ESD                      | No         |
| <b>Winter</b> Winter footwear                             | No         |
| <b>ANTICUT</b> Anti-cut boots                             | No         |
| <b>Standard</b>   | 20347:2012 |
| <b>Shoe marking</b>                                       | O2         |

## Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 38       | 0,96 kg    | 1,25 kg      | 230 mm            | 330 mm             | 120 mm             | 475 mm                  | 615 mm                   | 350 mm                   | 13,60 kg                 | 0,0 mm              |
| 39       | 0,98 kg    | 1,30 kg      | 230 mm            | 330 mm             | 120 mm             | 475 mm                  | 615 mm                   | 350 mm                   | 13,80 kg                 | 0,0 mm              |
| 40       | 1,03 kg    | 1,32 kg      | 230 mm            | 330 mm             | 120 mm             | 475 mm                  | 615 mm                   | 350 mm                   | 14,00 kg                 | 0,0 mm              |
| 41       | 1,04 kg    | 1,33 kg      | 230 mm            | 330 mm             | 120 mm             | 475 mm                  | 615 mm                   | 350 mm                   | 14,20 kg                 | 0,0 mm              |
| 42       | 1,11 kg    | 1,39 kg      | 230 mm            | 330 mm             | 120 mm             | 475 mm                  | 615 mm                   | 350 mm                   | 15,00 kg                 | 0,0 mm              |
| 43       | 1,13 kg    | 1,45 kg      | 240 mm            | 360 mm             | 125 mm             | 500 mm                  | 640 mm                   | 380 mm                   | 15,80 kg                 | 0,0 mm              |
| 44       | 1,19 kg    | 1,51 kg      | 240 mm            | 360 mm             | 125 mm             | 500 mm                  | 640 mm                   | 380 mm                   | 16,20 kg                 | 0,0 mm              |
| 45       | 1,21 kg    | 1,53 kg      | 240 mm            | 360 mm             | 125 mm             | 500 mm                  | 640 mm                   | 380 mm                   | 16,60 kg                 | 0,0 mm              |
| 46       | 1,26 kg    | 1,58 kg      | 240 mm            | 360 mm             | 125 mm             | 500 mm                  | 640 mm                   | 380 mm                   | 17,20 kg                 | 0,0 mm              |
| 47       | 1,30 kg    | 1,62 kg      | 240 mm            | 360 mm             | 125 mm             | 500 mm                  | 640 mm                   | 380 mm                   | 17,40 kg                 | 0,0 mm              |

## Business parameters

|                 |          |
|-----------------|----------|
| <b>Tarric</b>   | 64039993 |
| <b>Country</b>  | CN       |
| <b>Weight</b>   | 1,33 kg  |
| <b>Add Unit</b> | NPR      |

**Add Quantity** 1