

Technical sheet

TIRANA low cut occupational shoes

Product code: 3195-01



upper	brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
size	36 - 48
standard	EN ISO 20347:2012
version	O1 FO SRA - without steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	O1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,90 kg	1,17 kg	200 mm	315 mm	115 mm	435 mm	605 mm	325 mm	13,00 kg	244,0 mm
37	0,94 kg	1,20 kg	200 mm	315 mm	115 mm	435 mm	605 mm	325 mm	13,40 kg	251,0 mm
38	0,97 kg	1,23 kg	200 mm	315 mm	115 mm	435 mm	605 mm	325 mm	13,60 kg	259,0 mm
39	1,00 kg	1,27 kg	200 mm	315 mm	115 mm	435 mm	605 mm	325 mm	14,00 kg	266,0 mm
40	1,06 kg	1,30 kg	200 mm	315 mm	115 mm	435 mm	605 mm	325 mm	14,60 kg	272,0 mm
41	1,09 kg	1,35 kg	200 mm	315 mm	115 mm	435 mm	605 mm	325 mm	15,00 kg	279,0 mm
42	1,11 kg	1,36 kg	200 mm	315 mm	115 mm	435 mm	605 mm	325 mm	15,20 kg	286,0 mm
43	1,14 kg	1,40 kg	215 mm	330 mm	120 mm	435 mm	605 mm	325 mm	15,80 kg	293,0 mm
44	1,26 kg	1,54 kg	215 mm	330 mm	120 mm	435 mm	605 mm	325 mm	16,40 kg	299,0 mm
45	1,27 kg	1,54 kg	210 mm	355 mm	125 mm	440 mm	640 mm	370 mm	16,60 kg	305,0 mm
46	1,39 kg	1,58 kg	210 mm	355 mm	125 mm	440 mm	640 mm	370 mm	17,60 kg	314,0 mm
47	1,46 kg	1,76 kg	210 mm	355 mm	125 mm	440 mm	640 mm	370 mm	19,00 kg	320,0 mm
48	1,55 kg	1,85 kg	210 mm	355 mm	125 mm	440 mm	640 mm	370 mm	20,00 kg	327,0 mm

Business parameters

Tarric	64039993
Country	CN

Weight	1,36 kg
Add Unit	NPR
Add Quantity	1