

# Technical sheet

## BRUSEL ankle safety shoes

Product code: 2880-S1



<b>upper</b>	cowhide leather with pattern in a thickness of 1,8 - 2,0 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1 SRC - with steel toe cap

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,99 kg	1,21 kg	225 mm	315 mm	115 mm	475 mm	600 mm	335 mm	13,00 kg	239,0 mm
37	1,00 kg	1,23 kg	225 mm	315 mm	115 mm	475 mm	600 mm	335 mm	13,20 kg	245,7 mm
38	1,04 kg	1,25 kg	225 mm	315 mm	115 mm	475 mm	600 mm	335 mm	13,40 kg	252,3 mm
39	1,12 kg	1,30 kg	225 mm	315 mm	115 mm	475 mm	600 mm	335 mm	13,80 kg	259,0 mm
40	1,14 kg	1,32 kg	225 mm	315 mm	115 mm	475 mm	600 mm	335 mm	14,40 kg	265,7 mm
41	1,18 kg	1,39 kg	225 mm	315 mm	115 mm	475 mm	600 mm	335 mm	15,00 kg	272,3 mm
42	1,22 kg	1,43 kg	225 mm	315 mm	115 mm	475 mm	600 mm	335 mm	15,20 kg	279,0 mm
43	1,29 kg	1,51 kg	230 mm	330 mm	120 mm	475 mm	630 mm	360 mm	16,00 kg	285,7 mm
44	1,31 kg	1,54 kg	230 mm	330 mm	120 mm	475 mm	630 mm	360 mm	15,80 kg	292,3 mm
45	1,32 kg	1,56 kg	235 mm	330 mm	125 mm	495 mm	650 mm	370 mm	16,60 kg	299,0 mm
46	1,40 kg	1,64 kg	235 mm	350 mm	125 mm	495 mm	650 mm	370 mm	17,40 kg	305,7 mm
47	1,44 kg	1,68 kg	235 mm	350 mm	125 mm	495 mm	650 mm	370 mm	17,60 kg	312,4 mm
48	1,46 kg	1,71 kg	235 mm	350 mm	125 mm	495 mm	650 mm	370 mm	18,20 kg	319,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN

**Weight** 1,40 kg  
**Add Unit** NPR  
**Add Quantity** 1