

Technical sheet

FALUN high heel occupational shoes, winter design

Product code: 3290-O2W



upper	cowhide leather with pattern in a thickness of 1,6 - 1,8 mm
lining	hair plush DELTA
inner insole	anatomically shaped, coated with hair plush DELTA, antistatic
outsole	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
size	36 - 50
standard	EN ISO 20347:2022
version	O2W FO SR - without steel toe cap, winter design

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	Yes
ANTICUT Anti-cut boots	No
Standard	20347:2023
Shoe marking	O2

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,87 kg	1,19 kg	315 mm	315 mm	115 mm	600 mm	645 mm	340 mm	13,40 kg	0,0 mm
37	0,89 kg	1,21 kg	315 mm	315 mm	115 mm	600 mm	645 mm	340 mm	13,60 kg	0,0 mm
38	0,91 kg	1,20 kg	315 mm	315 mm	115 mm	600 mm	645 mm	340 mm	13,40 kg	0,0 mm
39	0,97 kg	1,28 kg	315 mm	315 mm	115 mm	600 mm	645 mm	340 mm	14,60 kg	0,0 mm
40	0,98 kg	1,27 kg	315 mm	315 mm	115 mm	600 mm	645 mm	340 mm	14,20 kg	0,0 mm
41	1,04 kg	1,34 kg	315 mm	315 mm	115 mm	600 mm	645 mm	340 mm	14,80 kg	0,0 mm
42	1,07 kg	1,38 kg	315 mm	315 mm	115 mm	600 mm	645 mm	340 mm	15,00 kg	0,0 mm
43	1,10 kg	1,42 kg	325 mm	330 mm	120 mm	630 mm	650 mm	345 mm	15,60 kg	0,0 mm
44	1,16 kg	1,48 kg	325 mm	350 mm	120 mm	630 mm	650 mm	345 mm	16,00 kg	0,0 mm
45	1,22 kg	1,56 kg	340 mm	350 mm	125 mm	650 mm	690 mm	370 mm	17,00 kg	0,0 mm
46	1,28 kg	1,61 kg	340 mm	350 mm	125 mm	650 mm	690 mm	370 mm	16,80 kg	0,0 mm
47	1,31 kg	1,65 kg	340 mm	350 mm	125 mm	650 mm	690 mm	370 mm	18,00 kg	0,0 mm
48	1,34 kg	1,69 kg	340 mm	350 mm	125 mm	650 mm	690 mm	370 mm	18,20 kg	0,0 mm
49	1,39 kg	1,74 kg	360 mm	370 mm	135 mm	715 mm	750 mm	400 mm	19,20 kg	0,0 mm
50	1,52 kg	1,87 kg	360 mm	370 mm	135 mm	715 mm	750 mm	400 mm	21,00 kg	0,0 mm

Business parameters

Tarric	64039113
Country	CN
Weight	1,47 kg
Add Unit	NPR
Add Quantity	1