

Technical sheet

VADUZ ankle occupational shoes, winter design

Product code: 2770-O2W



upper	cowhide suede leather NUBUCK in a thickness of 1,8 - 2,0 mm
lining	hair plush DELTA
inner insole	anatomically shaped with latex heel pad, coated with CAMBRELLA, antistatic
outsole	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
size	36 - 48
standard	EN ISO 20347:2012
version	O2W FO SRC - without steel toe cap, winter design

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	Yes
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	Yes
ANTICUT Anti-cut boots	No
Standard	20347:2012
Shoe marking	O2

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,04 kg	1,31 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	16,00 kg	244,0 mm
37	1,06 kg	1,34 kg	225 mm	315 mm	120 mm	475 mm	600 mm	300 mm	16,00 kg	251,0 mm
38	1,12 kg	1,37 kg	225 mm	315 mm	120 mm	475 mm	600 mm	300 mm	16,20 kg	259,0 mm
39	1,14 kg	1,40 kg	225 mm	315 mm	120 mm	475 mm	600 mm	300 mm	16,40 kg	266,0 mm
40	1,16 kg	1,45 kg	225 mm	315 mm	120 mm	475 mm	600 mm	300 mm	16,40 kg	272,0 mm
41	1,22 kg	1,51 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	16,60 kg	279,0 mm
42	1,25 kg	1,54 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	17,00 kg	286,0 mm
43	1,29 kg	1,60 kg	230 mm	330 mm	120 mm	490 mm	600 mm	330 mm	17,80 kg	293,0 mm
44	1,35 kg	1,66 kg	230 mm	330 mm	120 mm	490 mm	600 mm	330 mm	18,20 kg	299,0 mm
45	1,39 kg	1,99 kg	230 mm	330 mm	120 mm	490 mm	600 mm	330 mm	18,80 kg	305,0 mm
46	1,43 kg	1,77 kg	250 mm	360 mm	130 mm	505 mm	655 mm	380 mm	19,60 kg	314,0 mm
47	1,51 kg	1,85 kg	250 mm	360 mm	130 mm	505 mm	655 mm	380 mm	20,40 kg	320,0 mm
48	1,54 kg	1,87 kg	250 mm	360 mm	130 mm	505 mm	655 mm	380 mm	21,00 kg	327,0 mm

Business parameters

Tarric	64039113
Country	CN

Weight	1,50 kg
Add Unit	NPR
Add Quantity	1