

# Technical sheet

## GLASGOW high heel occupational shoes

Product code: 2390-02



<b>upper</b>	cowhide leather in a thickness of 2,0 - 2,2 mm
<b>lining</b>	laminated breathable fabric FLESH
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	37 - 48
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	O2 FO HRO SRC - without steel toe cap and midsole, hydrophobic

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	Yes
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2012
<b>Shoe marking</b>	O2

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	1,30 kg	1,60 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	17,70 kg	237,0 mm
38	1,34 kg	1,65 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	18,00 kg	244,5 mm
39	1,37 kg	1,73 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	18,40 kg	252,0 mm
40	1,39 kg	1,76 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	18,80 kg	259,5 mm
41	1,43 kg	1,79 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	19,20 kg	267,0 mm
42	1,47 kg	1,83 kg	320 mm	315 mm	120 mm	600 mm	645 mm	350 mm	19,60 kg	274,5 mm
43	1,54 kg	1,94 kg	330 mm	350 mm	125 mm	655 mm	675 mm	380 mm	21,00 kg	282,0 mm
44	1,56 kg	1,96 kg	330 mm	350 mm	125 mm	655 mm	675 mm	380 mm	21,60 kg	289,5 mm
45	1,68 kg	2,09 kg	330 mm	350 mm	125 mm	655 mm	675 mm	380 mm	22,60 kg	297,0 mm
46	1,77 kg	2,17 kg	330 mm	350 mm	125 mm	655 mm	675 mm	380 mm	24,20 kg	304,5 mm
47	1,83 kg	2,24 kg	330 mm	350 mm	125 mm	655 mm	675 mm	380 mm	24,00 kg	312,0 mm
48	1,94 kg	2,35 kg	330 mm	350 mm	125 mm	655 mm	675 mm	380 mm	25,00 kg	319,5 mm

## Business parameters

<b>Tarric</b>	64039113
<b>Country</b>	CN

**Weight** 1,89 kg  
**Add Unit** NPR  
**Add Quantity** 1