

# Technical sheet

## HALIFAX ankle safety shoes



Product code: 2710-S3



<b>upper</b>	cowhide leather in a thickness of 2,0 - 2,2 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S3 HRO SRC - with composite toe cap and kevlar midsole

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	Yes
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S3

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,10 kg	1,32 kg	225 mm	315 mm	115 mm	470 mm	600 mm	345 mm	13,60 kg	233,0 mm
37	1,15 kg	1,37 kg	225 mm	315 mm	115 mm	470 mm	600 mm	345 mm	14,10 kg	239,7 mm
38	1,21 kg	1,45 kg	225 mm	315 mm	115 mm	470 mm	600 mm	345 mm	14,70 kg	246,3 mm
39	1,22 kg	1,49 kg	230 mm	315 mm	115 mm	470 mm	595 mm	340 mm	16,40 kg	253,0 mm
40	1,25 kg	1,52 kg	230 mm	315 mm	115 mm	470 mm	595 mm	340 mm	16,60 kg	259,7 mm
41	1,29 kg	1,55 kg	230 mm	315 mm	115 mm	470 mm	595 mm	340 mm	16,80 kg	266,3 mm
42	1,32 kg	1,58 kg	230 mm	315 mm	115 mm	470 mm	595 mm	340 mm	17,00 kg	273,0 mm
43	1,42 kg	1,68 kg	230 mm	330 mm	125 mm	480 mm	635 mm	350 mm	18,00 kg	279,7 mm
44	1,48 kg	1,74 kg	230 mm	330 mm	125 mm	480 mm	635 mm	350 mm	18,60 kg	286,3 mm
45	1,56 kg	1,83 kg	230 mm	330 mm	125 mm	480 mm	635 mm	350 mm	19,40 kg	293,0 mm
46	1,60 kg	1,91 kg	235 mm	350 mm	125 mm	490 mm	650 mm	370 mm	20,20 kg	299,7 mm
47	1,63 kg	1,93 kg	235 mm	350 mm	125 mm	490 mm	650 mm	370 mm	20,80 kg	306,4 mm
48	1,67 kg	1,99 kg	235 mm	350 mm	125 mm	490 mm	650 mm	370 mm	21,00 kg	313,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN

<b>Weight</b>	1,80 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1