

# Technical sheet

## VADUZ ankle occupational shoes

Product code: 2770-01



<b>upper</b>	cowhide suede leather NUBUCK in a thickness of 1,8 - 2,0 mm
<b>lining</b>	CAMBRELLA fabric with absorbency
<b>inner insole</b>	anatomically shaped with latex heel pad, coated with CAMBRELLA, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	O1 FO SRC - without steel toe cap

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2012
<b>Shoe marking</b>	O1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,96 kg	1,20 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	13,20 kg	244,0 mm
37	0,97 kg	1,23 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	13,30 kg	251,0 mm
38	1,00 kg	1,26 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	13,60 kg	259,0 mm
39	1,05 kg	1,30 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	13,80 kg	266,0 mm
40	1,23 kg	1,51 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	16,80 kg	272,0 mm
41	1,25 kg	1,53 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	16,80 kg	279,0 mm
42	1,32 kg	1,60 kg	225 mm	315 mm	120 mm	475 mm	600 mm	330 mm	17,80 kg	286,0 mm
43	1,36 kg	1,66 kg	230 mm	330 mm	120 mm	490 mm	625 mm	360 mm	16,40 kg	293,0 mm
44	1,41 kg	1,72 kg	230 mm	330 mm	120 mm	490 mm	625 mm	360 mm	18,80 kg	299,0 mm
45	1,44 kg	1,75 kg	230 mm	330 mm	120 mm	490 mm	625 mm	360 mm	19,20 kg	305,0 mm
46	1,51 kg	1,83 kg	250 mm	360 mm	130 mm	505 mm	655 mm	380 mm	20,00 kg	314,0 mm
47	1,58 kg	1,91 kg	250 mm	360 mm	130 mm	505 mm	655 mm	380 mm	20,80 kg	320,0 mm
48	1,64 kg	1,97 kg	250 mm	360 mm	130 mm	505 mm	655 mm	380 mm	21,40 kg	327,0 mm

## Business parameters

<b>Tarric</b>	64039113
<b>Country</b>	CN

<b>Weight</b>	1,45 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1