

# Technical sheet

## MASKAT ankle safety shoes



Product code: 5440-S1P



<b>upper</b>	brushed cow suede leather, coated in a thickness of 1,8 - 2,0 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1P HRO SRA - with composite toe cap and kevlar midsole

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	Yes
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	Yes
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,27 kg	1,58 kg	260 mm	320 mm	115 mm	550 mm	600 mm	340 mm	16,80 kg	0,0 mm
37	1,30 kg	1,61 kg	260 mm	320 mm	115 mm	550 mm	600 mm	340 mm	17,00 kg	0,0 mm
38	1,35 kg	1,66 kg	260 mm	320 mm	115 mm	550 mm	600 mm	340 mm	17,40 kg	0,0 mm
39	1,27 kg	1,54 kg	225 mm	315 mm	115 mm	475 mm	595 mm	335 mm	16,20 kg	253,0 mm
40	1,34 kg	1,60 kg	225 mm	315 mm	115 mm	475 mm	595 mm	335 mm	16,40 kg	259,7 mm
41	1,38 kg	1,62 kg	225 mm	315 mm	115 mm	475 mm	595 mm	335 mm	17,00 kg	266,3 mm
42	1,43 kg	1,70 kg	225 mm	315 mm	115 mm	475 mm	595 mm	335 mm	17,60 kg	273,0 mm
43	1,57 kg	1,84 kg	230 mm	330 mm	120 mm	480 mm	615 mm	350 mm	18,40 kg	279,7 mm
44	1,60 kg	1,87 kg	230 mm	330 mm	120 mm	480 mm	615 mm	350 mm	19,20 kg	286,3 mm
45	1,61 kg	1,89 kg	230 mm	330 mm	120 mm	480 mm	615 mm	350 mm	19,60 kg	293,0 mm
46	1,64 kg	1,95 kg	235 mm	350 mm	125 mm	495 mm	650 mm	390 mm	20,40 kg	299,7 mm
47	1,74 kg	2,05 kg	235 mm	350 mm	125 mm	495 mm	650 mm	390 mm	21,40 kg	306,4 mm
48	1,79 kg	2,11 kg	235 mm	350 mm	125 mm	495 mm	650 mm	390 mm	21,80 kg	313,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN

<b>Weight</b>	1,67 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1