

Technical sheet

ROCKFORD ankle safety shoes



Product code: 7140-S3



upper	cowhide leather CRAZY HORSE in a thickness 2,0 - 2,2 mm
lining	breathable thermo-insulation MEMBRANE FREE-TEX®
inner insole	expanded polyurethane of high absorbency, antistatic
outsole	MICHELIN®-PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic
size	39 - 48
standard	EN ISO 20345:2011
version	S3 HRO SRC CI WR - with composite toe cap and kevlar midsole, hydrophobic, FREE-TEX®, Boa® Fit System

Properties

PL Midsole penetration protection nonmetalic - PL	No
PS Midsole penetration protection nonmetalic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	Yes
WR Water resistant	Yes
WRU Water resistant upper	Yes
CI Insulation against cold	Yes
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	Yes
SRC Antislip resistance SRA + SRB	Yes
Free-tex Membrane	Yes
Michelin Michelin® sole	Yes
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,72 kg	2,05 kg	280 mm	330 mm	125 mm	565 mm	650 mm	360 mm	21,80 kg	256,0 mm
40	1,77 kg	2,11 kg	270 mm	330 mm	125 mm	565 mm	650 mm	360 mm	22,00 kg	262,7 mm
41	1,78 kg	2,13 kg	270 mm	330 mm	125 mm	565 mm	650 mm	360 mm	23,00 kg	269,3 mm
42	1,90 kg	2,26 kg	270 mm	330 mm	125 mm	565 mm	650 mm	360 mm	23,60 kg	276,0 mm
43	1,92 kg	2,30 kg	270 mm	330 mm	125 mm	565 mm	650 mm	360 mm	24,20 kg	282,7 mm
44	1,99 kg	2,41 kg	280 mm	360 mm	135 mm	585 mm	680 mm	390 mm	25,60 kg	289,3 mm
45	2,07 kg	2,44 kg	280 mm	360 mm	135 mm	585 mm	680 mm	390 mm	26,00 kg	296,0 mm
46	2,15 kg	2,54 kg	280 mm	360 mm	135 mm	585 mm	680 mm	390 mm	27,00 kg	302,7 mm
47	2,20 kg	2,61 kg	280 mm	360 mm	135 mm	585 mm	680 mm	390 mm	27,40 kg	309,4 mm
48	2,33 kg	2,73 kg	280 mm	360 mm	135 mm	585 mm	680 mm	390 mm	28,40 kg	316,0 mm

Business parameters

Tarric	64034000
Country	CN
Weight	2,15 kg
Add Unit	NPR

Add Quantity 1