

# Technical sheet

## SANTIAGO ankle occupational shoes

Product code: 4170-02



<b>upper</b>	cowhide leather NUBUCK in a thickness of 1,9 - 2,1 mm
<b>lining</b>	breathable thermo-insulation MEMBRANE FREE-TEX®
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	EVA/RUBBER - resistant to fuel oils, antistatic, antislip, glued construction
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	OB E WRU SRA - without steel toe cap, hydrophobic, FREE-TEX®

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	Yes
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2012
<b>Shoe marking</b>	OB

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,03 kg	1,30 kg	270 mm	315 mm	110 mm	570 mm	580 mm	335 mm	14,30 kg	240,1 mm
37	1,06 kg	1,35 kg	270 mm	315 mm	110 mm	570 mm	580 mm	335 mm	14,60 kg	246,8 mm
38	1,12 kg	1,41 kg	270 mm	315 mm	110 mm	570 mm	580 mm	335 mm	15,20 kg	253,5 mm
39	1,14 kg	1,44 kg	270 mm	315 mm	110 mm	570 mm	580 mm	335 mm	15,80 kg	260,1 mm
40	1,19 kg	1,49 kg	270 mm	315 mm	110 mm	570 mm	580 mm	335 mm	16,00 kg	266,8 mm
41	1,21 kg	1,21 kg	270 mm	315 mm	110 mm	570 mm	580 mm	335 mm	16,20 kg	273,5 mm
42	1,26 kg	1,60 kg	290 mm	345 mm	125 mm	610 mm	630 mm	365 mm	17,60 kg	280,1 mm
43	1,30 kg	1,66 kg	290 mm	345 mm	125 mm	610 mm	630 mm	365 mm	18,40 kg	286,8 mm
44	1,39 kg	1,73 kg	290 mm	345 mm	125 mm	610 mm	630 mm	365 mm	19,00 kg	293,5 mm
45	1,46 kg	1,81 kg	290 mm	345 mm	125 mm	610 mm	630 mm	365 mm	19,60 kg	300,1 mm
46	1,53 kg	1,92 kg	305 mm	370 mm	130 mm	650 mm	650 mm	390 mm	20,80 kg	306,8 mm
47	1,55 kg	1,93 kg	305 mm	370 mm	130 mm	650 mm	650 mm	390 mm	21,00 kg	313,5 mm
48	1,56 kg	1,95 kg	305 mm	370 mm	130 mm	650 mm	650 mm	390 mm	21,20 kg	320,2 mm

## Business parameters

<b>Tarric</b>	64039113
<b>Country</b>	CN

**Weight** 1,70 kg  
**Add Unit** NPR  
**Add Quantity** 1