

# Technical sheet

## SHEFFIELD high heel occupational shoes, winter design

Product code: 2890-O2W



<b>upper</b>	cowhide leather with pattern in a thickness of 1,8 - 2,0 mm
<b>lining</b>	hair plush DELTA
<b>inner insole</b>	anatomically shaped, coated with hair plush DELTA, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20347:2012
<b>version</b>	O2W FO CI SRC - without steel toe cap, winter design

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	Yes
<b>CI</b> Insulation against cold	Yes
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	Yes
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2012
<b>Shoe marking</b>	O2

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,01 kg	1,19 kg	315 mm	315 mm	115 mm	595 mm	640 mm	330 mm	13,70 kg	240,5 mm
37	1,02 kg	1,31 kg	315 mm	315 mm	115 mm	595 mm	640 mm	330 mm	14,40 kg	247,2 mm
38	1,08 kg	1,35 kg	315 mm	315 mm	115 mm	595 mm	640 mm	330 mm	14,90 kg	253,8 mm
39	1,10 kg	1,38 kg	315 mm	315 mm	115 mm	595 mm	640 mm	330 mm	15,30 kg	260,5 mm
40	1,14 kg	1,43 kg	315 mm	315 mm	115 mm	595 mm	640 mm	330 mm	15,90 kg	267,2 mm
41	1,20 kg	1,49 kg	315 mm	315 mm	115 mm	595 mm	640 mm	330 mm	16,20 kg	273,8 mm
42	1,21 kg	1,49 kg	315 mm	315 mm	115 mm	595 mm	640 mm	330 mm	16,20 kg	280,5 mm
43	1,31 kg	1,63 kg	325 mm	325 mm	125 mm	620 mm	660 mm	350 mm	17,40 kg	287,2 mm
44	1,33 kg	1,64 kg	325 mm	325 mm	125 mm	620 mm	660 mm	350 mm	17,60 kg	293,8 mm
45	1,35 kg	1,68 kg	325 mm	325 mm	125 mm	620 mm	660 mm	350 mm	18,20 kg	300,5 mm
46	1,41 kg	1,75 kg	340 mm	350 mm	125 mm	645 mm	690 mm	370 mm	18,80 kg	307,2 mm
47	1,42 kg	1,75 kg	340 mm	350 mm	125 mm	645 mm	690 mm	370 mm	19,20 kg	313,9 mm
48	1,49 kg	1,82 kg	340 mm	350 mm	125 mm	645 mm	690 mm	370 mm	19,90 kg	320,5 mm

## Business parameters

<b>Tarric</b>	64039113
<b>Country</b>	CN

<b>Weight</b>	1,47 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1