

Technical sheet

TENERIFE low cut safety shoes

Product code: 4795-S1P



upper	synthetic, brushed EKO VELUR material, abrasion resistant
lining	laminated breathable fabric MESH
inner insole	HI-POLY - anatomically shaped, lightweight polyurethane foam coated with fabric MESH, antistatic
outsole	EVA/RUBBER - glued construction
size	39 - 48
standard	EN ISO 20345:2011
version	S1P SRA - with plastic toe cap and kevlar midsole, NON METALLIC

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	Yes
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2012
Shoe marking	S1

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	1,02 kg	1,36 kg	210 mm	320 mm	115 mm	450 mm	615 mm	350 mm	15,20 kg	257,0 mm
40	1,11 kg	1,46 kg	210 mm	320 mm	115 mm	450 mm	615 mm	350 mm	16,00 kg	257,0 mm
41	1,13 kg	1,47 kg	230 mm	320 mm	120 mm	495 mm	635 mm	350 mm	16,60 kg	257,0 mm
42	1,18 kg	1,57 kg	230 mm	320 mm	120 mm	495 mm	635 mm	350 mm	17,60 kg	257,0 mm
43	1,21 kg	1,59 kg	230 mm	320 mm	120 mm	495 mm	635 mm	350 mm	18,20 kg	257,0 mm
44	1,27 kg	1,66 kg	230 mm	320 mm	120 mm	495 mm	635 mm	350 mm	18,60 kg	257,0 mm
45	1,31 kg	1,70 kg	250 mm	340 mm	130 mm	535 mm	695 mm	375 mm	19,00 kg	257,0 mm
46	1,35 kg	1,78 kg	250 mm	340 mm	130 mm	535 mm	695 mm	375 mm	19,80 kg	257,0 mm
47	1,42 kg	1,85 kg	250 mm	340 mm	130 mm	535 mm	695 mm	375 mm	20,60 kg	257,0 mm
48	1,47 kg	1,90 kg	270 mm	370 mm	130 mm	570 mm	685 mm	400 mm	20,80 kg	257,0 mm

Business parameters

Tarric	64041990
Country	BD
Weight	1,45 kg
Add Unit	NPR

Add Quantity 1