

# Technical sheet

## LYON safety sandal

Product code: 2225-S1ESD



<b>upper</b>	brushed cow suede leather, coated in a thickness of 1,8 - 2,0 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011, EN ISO 61340-5-1:2016
<b>version</b>	S1 ESD SRC - with aluminium toe cap - antistatic properties ESD

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	Yes
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,82 kg	1,10 kg	210 mm	320 mm	120 mm	440 mm	600 mm	350 mm	12,00 kg	235,0 mm
37	0,84 kg	1,12 kg	210 mm	320 mm	120 mm	440 mm	600 mm	350 mm	12,20 kg	242,0 mm
38	0,89 kg	1,16 kg	210 mm	320 mm	120 mm	440 mm	600 mm	350 mm	12,60 kg	250,0 mm
39	0,94 kg	1,22 kg	210 mm	320 mm	120 mm	440 mm	600 mm	350 mm	13,20 kg	257,0 mm
40	0,96 kg	1,24 kg	210 mm	320 mm	120 mm	440 mm	600 mm	350 mm	13,60 kg	265,0 mm
41	1,02 kg	1,29 kg	210 mm	320 mm	120 mm	440 mm	600 mm	350 mm	14,00 kg	272,0 mm
42	1,06 kg	1,33 kg	210 mm	320 mm	120 mm	440 mm	600 mm	350 mm	14,60 kg	280,0 mm
43	1,08 kg	1,40 kg	230 mm	350 mm	130 mm	470 mm	645 mm	370 mm	15,20 kg	287,0 mm
44	1,11 kg	1,43 kg	230 mm	350 mm	130 mm	470 mm	645 mm	370 mm	15,80 kg	295,0 mm
45	1,26 kg	1,60 kg	230 mm	350 mm	130 mm	470 mm	645 mm	370 mm	17,00 kg	302,0 mm
46	1,29 kg	1,61 kg	230 mm	350 mm	130 mm	470 mm	645 mm	370 mm	16,60 kg	310,0 mm
47	1,31 kg	1,63 kg	230 mm	350 mm	130 mm	470 mm	645 mm	370 mm	17,40 kg	317,0 mm
48	1,36 kg	1,68 kg	230 mm	350 mm	130 mm	470 mm	645 mm	370 mm	17,80 kg	325,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN

**Weight** 1,30 kg  
**Add Unit** NPR  
**Add Quantity** 1