

# Technical sheet

## COVENTRY low cut safety shoes



Product code: 5065-S1



<b>upper</b>	cowhide leather with pattern in a thickness of 1,8 - 2,0 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	anatomically shaped from material EVA with a high absorbency, antistatic
<b>outsole</b>	PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	36 - 48
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1 HRO SRC - with steel toe cap

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	Yes
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	Yes
<b>SRC</b> Antislip resistance SRA + SRB	Yes
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	1,10 kg	1,34 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	13,60 kg	233,0 mm
37	1,12 kg	1,37 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	13,80 kg	239,7 mm
38	1,18 kg	1,40 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	14,40 kg	246,3 mm
39	1,21 kg	1,44 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	14,80 kg	253,0 mm
40	1,21 kg	1,46 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	15,00 kg	259,7 mm
41	1,26 kg	1,49 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	15,80 kg	266,3 mm
42	1,27 kg	1,50 kg	200 mm	315 mm	115 mm	420 mm	600 mm	330 mm	16,20 kg	273,0 mm
43	1,35 kg	1,61 kg	205 mm	330 mm	115 mm	430 mm	605 mm	350 mm	16,80 kg	279,7 mm
44	1,42 kg	1,68 kg	205 mm	330 mm	115 mm	430 mm	605 mm	350 mm	17,20 kg	286,3 mm
45	1,48 kg	1,73 kg	205 mm	330 mm	115 mm	430 mm	605 mm	350 mm	18,40 kg	293,0 mm
46	1,49 kg	1,76 kg	210 mm	355 mm	125 mm	440 mm	640 mm	365 mm	19,00 kg	299,7 mm
47	1,56 kg	1,84 kg	210 mm	355 mm	125 mm	440 mm	640 mm	365 mm	19,60 kg	306,4 mm
48	1,60 kg	1,90 kg	210 mm	355 mm	125 mm	440 mm	640 mm	365 mm	20,00 kg	313,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN

**Weight** 1,57 kg  
**Add Unit** NPR  
**Add Quantity** 1